



Intelligence Surveillance and Reconnaissance Asset Assignment for Optimal Mission Effectiveness

Capt Ryan Kappedal, M.S. Maj August Roesener, Ph.D. Maj Shane Hall, Ph.D.

> Sponsor USSTRATCOM

maintaining the data needed, and c including suggestions for reducing	election of information is estimated to completing and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding ar OMB control number.	ion of information. Send comments arters Services, Directorate for Info	regarding this burden estimate mation Operations and Reports	or any other aspect of the property of the contract of the con	nis collection of information, Highway, Suite 1204, Arlington			
1. REPORT DATE 01 JUN 2008		2. REPORT TYPE N/A		3. DATES COVERED				
4. TITLE AND SUBTITLE				5a. CONTRACT	NUMBER			
Intelligence Survei Optimal Mission E	llance and Reconna	ment for	5b. GRANT NUM	MBER				
Optimal Wission E	anecuveness		5c. PROGRAM E	ELEMENT NUMBER				
6. AUTHOR(S)				5d. PROJECT NU	JMBER			
				5e. TASK NUMBER				
			5f. WORK UNIT NUMBER					
7. PERFORMING ORGANI Air Force Institute	ZATION NAME(S) AND AD of Technology		8. PERFORMING ORGANIZATION REPORT NUMBER					
9. SPONSORING/MONITO	RING AGENCY NAME(S) A	AND ADDRESS(ES)		10. SPONSOR/MONITOR'S ACRONYM(S)				
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)				
12. DISTRIBUTION/AVAIL Approved for publ	LABILITY STATEMENT ic release, distributi	on unlimited						
	OTES 27. Military Operat ne 10-12, 2008, The		• • •		New London,			
14. ABSTRACT								
15. SUBJECT TERMS								
16. SECURITY CLASSIFIC	CATION OF:	17. LIMITATION OF ABSTRACT	18. NUMBER	19a. NAME OF				
a. REPORT unclassified				OF PAGES 29	RESPONSIBLE PERSON			

Report Documentation Page

Form Approved OMB No. 0704-0188





24/29/2008 03:19

7035886232

AF / 49


GOVERNMENT DISCLOSURE FORM	12B MORS P#: gracomo 12B DEADLINE: 2 MAY DS First to: 703-933-908
Principal Author: Other Author(e):	
Ryan Kappedal August Roes	sener, Shane Hall
HQ AF/A9	Run It Frall
	nelpel Author's Signature: 4 Date: 29 Apr 08
	ne: (703) 586-6916
FAS	
Title of Presentation:	of: ryar.kappedal@pentagon.af.mil
ISR Asset Assignment for Optima	Mission Effectiveness
This presentation is believed to be: SECRET CONFIDENTIAL	/ LINE STOLLES
	Listall WG(s) Ø: 1,4,7
(PARTIES AND ADDRESS OF A STREET AND ADDRESS OF A STRE	no to 0 Ohie tive 5,230 at 1 persons appeared
The Releasing Official, with the understanding that MORS Symposia are supervised by	
clearances of etteest SECRET and that on femilian nationals will be present confirms that	the overall classification of the presentation is.
SECRET COMPIDENTIAL UNCLASSIFIED OTHER:	and authorizes disclosure at the meeting
Classified by Declassified b	w:
Downgrade to:	Ox
The applicable distribution statement before must be checked	and stated to complete this form.
Distribution statement A: Other distribution st.	afement: (Ust tare or attach seporate pheet)
This propertialization/paper a unclassified approved for guests release, distribution unimited, and is economic toom U.S. expect summing and other appoint operation to the first toom of the second papers to the toom of the second papers of	
Rolosing Official's file PUBLIC AFFRIRS SPECIALIST	* Tativaque
Printed name: PAT LUAGNER	Reference Official's Signature: 4
Organization: O = 1 = 1 p.o.	
Organization: AFIT/PA	Date: 29 Rpv 28
Complete making address: 2950 Hobsoni WAY WPA-F13. OH 45433	Phone: (437) 255-4545-X4374



Problem Statement



- USSTRATCOM has requested assistance assigning sensors to multi-stage missions
- Each mission has several stages, and some sensors may be shared between missions
- Each sensor has a distinct probability of success at a unique mission's stage
 - These probabilities are not always known until just prior to tasking






Problem Example



Set of missions





General Mathematical Description

$$\max_{\mathbf{x}\in\Omega}F(\mathbf{x}),$$

$$\mathbf{x} \in \mathbb{B}^n$$


$$F(\mathbf{x}) \in \mathbb{R}^p$$

- This research seeks to
 - Define $\mathbf{x} \in \mathbb{B}^n$, $\mathbf{x} \in \Omega$, and $F(\mathbf{x})$
 - Find techniques to Maximize $F(\mathbf{x})$



Reliability Theory






$$R = [1 - (1 - P(E_{11}))(1 - P(E_{21}))][P(E_{12})]$$

- Basic bridge structure network
 - Assuming independent failures of elements,
 calculations are simple



Reliability Theory





- General bridge network
 - System is called a series-parallel redundant system



Simple Resource Allocation



$$\max \sum_{j=1}^{n} f_j(x_j),$$

subject to

$$\sum_{j=1}^{n} x_j \le b$$
$$\mathbf{x} \in \mathbb{Z}^n$$

- $f_i(x_i)$ is concave, increasing, and non-linear
- Problem is NP-Complete



Weighted Sum Scalarization



$$\max_{\mathbf{x} \in \Omega} \sum_{k=1}^{p} \lambda_k f_k(\mathbf{x}),$$
$$\mathbf{x} \in \mathbb{B}^n$$
$$f(\mathbf{x}) \in \mathbb{R}$$

- Converts a multi-objective function into a single objective function
- Answers are guaranteed to be efficient



Methodology



- Formulation of Maximum Utility Sensor Assignment Problem (MUSAP) as an IP
- Solution techniques
 - Explicit enumeration
 - Heuristics (Simulated Annealing)



Model Formulation




$$x_{ijk} \equiv \begin{cases} 1 & \text{if sensor } i \text{ is assigned to mission } j, \text{ at stage } k \\ 0 & \text{otherwise.} \end{cases}$$

Decision Variables

- Current formulation assumes any sensor can do any mission at any stage
- Each assignment has a probability of success, ρ_{ijk}



Building the Objective Function



- General bridge structure network for a single mission
 - Assumes independence of stages and sensors



Building the Objective Function



$$1 - \prod_{i=1}^{\alpha} (1 - \rho_{ijk} x_{ijk})$$

Probability of success at an individual stage

$$\prod_{k=1}^{\chi} \left(1 - \prod_{i=1}^{\alpha} (1 - \rho_{ijk} x_{ijk}) \right)$$

Probability of success at an individual mission

$$\sum_{j=1}^{\beta} w_j \left(\prod_{k=1}^{\chi} \left[1 - \prod_{i=1}^{\alpha} (1 - \rho_{ijk} x_{ijk}) \right] \right)$$

Mission probabilities aggregated into a weighted-sum scalarized objective function



Constraining the Space



$$\sum_{i=1}^{\alpha} \sum_{j=1}^{\beta} x_{ijk} \le \alpha \quad \forall \ k = 1, 2, \dots, \chi$$

Do not assign more sensors than are available at a given stage

$$\sum_{i \neq j} x_{ijk} \le 1 \ \forall i = 1, 2, \dots, \alpha, \ k = 1, 2, \dots, \chi$$

Do not assign a sensor to more than one mission at a given stage



Complete Formulation of MUSAP

$$\max \sum_{j=1}^{\beta} w_j \left(\prod_{k=1}^{\chi} \left[1 - \prod_{i=1}^{\alpha} (1 - \rho_{ijk} x_{ijk}) \right] \right)$$

subject to:

$$\sum_{i=1}^{\beta} \sum_{j=1}^{\alpha} x_{ijk} \le \alpha \quad \forall \quad k = 1, 2, \dots, \chi$$

$$\sum_{j=1}^{\beta} x_{ijk} \le 1 \quad \forall \quad i = 1, 2, \dots, \alpha, \quad k = 1, 2, \dots, \chi$$

$$x_{ijk} \in \{0, 1\} \quad \forall \quad i = 1, 2, \dots, \alpha, \quad j = 1, 2, \dots, \beta, \quad k = 1, 2, \dots, \chi$$



Intractability of test Problems



sensors	missions	stages	number of points
10	4	4	1.05×10^{6}
10	7	4	2.82×10^{8}
20	8	4	1.15×10^{18}
20	14	4	8.37×10^{22}
30	12	4	2.37×10^{32}
30	21	4	4.64×10^{39}
40	16	4	1.46×10^{48}
40	28	4	7.70×10^{57}



Heuristic Techniques




- Construction Heuristics
 - Greedy Individual and Greedy Marginal
- Local Search
 - Simulated Annealing (with several parameter settings)
- Combining Greedy Construction algorithms with Local search is a method called GRASP (Feo and Resende 1989)



Neighborhoods







Experimental Settings



Experimental Factors								
neighborhood	γ	starting point	diversify after					
1-swap	0 (Simple Ascent)	marginal	50%					
2-swap	0.9 (Simulated Annealing)	individual	75%					
3-swap	0.8 (Simulated Annealing)	-	never					
-	0.7 (Simulated Annealing)	-	-					

• 72 total algorithms

$$(3 \times 4 \times 2 \times 3 = 72)$$



Full Enumeration



- Provides a baseline from comparison of heuristics techniques
- Generally takes a large number of function evaluations
 - Every point must be examined
- Not practical for implementation



	Aggregate Results												
	Diversification Rule				Neighborhood			γ				Construction	
dist	50%	75%	never	1-swp	2-swp	3-swp	0.9	0.9 0.8 0.7 0				Ind	
10%	94.9%	94.8%	94.9%	91.2%	95.6%	97.9%	99.0%	96.6%	95.0%	88.9%	95.0%	94.8%	
5%	86.6%	86.9%	87.8%	82.9%	89.1%	89.4%	88.4%	88.2%	87.2%	84.7%	86.9%	87.4%	
1%	12.9%	14.2%	17.4%	16.1%	17.8%	10.6%	9.8%	14.0%	15.3%	20.1%	13.5%	16.1%	

Table B.3 Aggregate results for problem size $10 \times 4 \times 4$

	Aggregate Results											
	Diversification Rule			Neighborhood			γ				Construction	
$_{ m dist}$	50%	75%	never	1-swp	2-swp	3-swp	0.9	0.9 0.8 0.7 0				\mathbf{Ind}
10%	7.1%	7.3%	7.4%	3.8%	8.2%	9.7%	9.6%	5.0%	3.4%	10.9%	6.7%	7.7%
5%	0.4%	0.4%	0.5%	0.1%	0.5%	0.6%	0.5%	0.2%	0.2%	0.8%	0.3%	0.5%
1%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%

Table B.5 Aggregate results for problem size $10 \times 7 \times 4$

Sensor sparse networks have much worse results



Initial Results



- 10 x 4 x 4 network does well
- 10 x 7 x 4 network does poorly
 - Even with 7x the iterations
- Re-evaluating the SA algorithm
 - If the last sensor is removed from any individual mission's stage, the mission fails
 - A failed mission is very difficult to recover to a successful stage
 - Many local optima are created
 - Move evident in "sparse" vs. "saturated" networks
- Modification prevents "auto-fails" the every mission and stage has at least one sensor
 - This eliminates the "greedy individual constructions"
 - Only 36 algorithms to consider



Modified Algorithm (Saturated Network)

	Aggregate Results											
Diversification Rule Neighborhood							_	γ				
dist	50%	75%	never	1-swp	2-swp	3-swp	0.9	0.8	0.7	0		
10%	99.6%	99.7%	99.7%	99.3%	99.9%	99.8%	99.6%	99.6%	99.7%	99.7%		
5%	91.1%	91.6%	92.2%	89.7%	93.5%	91.7%	89.7%	90.5%	91.8%	94.5%		
1%	12.2%	14.2%	17.1%	15.7%	18.2%	9.7%	9.9%	14.7%	16.1%	17.3%		


Table B.7 Aggregate results for problem size $10 \times 4 \times 4$: Algorithm Modification

	Aggregate Results												
Diversification Rule Neighborhood								-	γ				
dist	50%	75%	never	1-swp	2-swp	3-swp	0.9 0.8 0.7 0						
10%	60.5%	60.2%	61.3%	47.8%	71.0%	63.1%	63.9%	60.7%	60.0%	58.0%			
5%	21.5%	21.7%	24.4%	16.3%	31.2%	20.0%	23.4%	21.9%	22.2%	22.5%			
1%	0.6%	0.8%	1.2%	0.5%	1.5%	0.5%	0.7%	0.7%	0.8%	1.1%			


Table B.9 Aggregate results for problem size 10×7×4: Algorithm Modification



Simulated Annealing Convergence



10x4x4 Network



10x7x4 Network



Overall Heuristics Observations

- Algorithm Type and Cooling Schedule
 - SA with a cooling schedule of 0.9 produces the highest quality results only in the sparse networks
 - In saturated networks, the Simple Ascent algorithm is more effective at returning high quality solutions.
 - May be because sensor saturated networks have far less local optimal than the sensor sparse networks



Overall Heuristics Observations

Neighborhood Functions

- 1-swap and 2-swap neighborhoods proved to be the best neighborhoods by consistently performing well in the test problems
- Larger neighborhoods performed very poorly, especially in the larger problem sizes
- In the larger neighborhoods, there are many different points to search with higher n-swap neighborhoods such that the probability of finding improving moves is smaller
- In this case, the simpler methods are better.



Overall Heuristics Observations

Diversification Rules

- "Never diversify" is the best rule
- Implication for MUSAP is that starting off with a strategy and utilizing it throughout, the algorithm performs much better than attempting to switch midstream.
- Does not rule out the possibility of using a different type of diversification strategy that doesn't use the "switch after certain percentage of iterations" rule.



Conclusions



- This research has formulated the USSTRATCOM's sensor assignment problem as a type of resource allocation problem.
 - Shown the utility of simulated annealing and simple ascent (iterative improvement) to solve that formulation.
 - As the problems became more complex, simulated annealing with geometric cooling schedules emerged as the most effective algorithm



Recommended Future Research

- Inserting Dependant Probabilities
 - Another effort has created this function
- Simulated Annealing Parameter Specification
 - 10x outer loop / inner loop ratio could be changed
- Varying Weights
 - Mission Drop thresholds
- Other Heuristics Techniques
 - GA has been successful in the single variable case